



Product Data Sheet

High Pressure Tubes

DESCRIPTION
Waterproof
ISO 9001: 2008 Certified Quality System
Length: 6m
Up to 4.140 bar (60.000 PSI)



CHARACTERISTICS
Certification EN 10201 3.1
Operating temperature range -252°C to +649°C
Stainless Steel 316 L - 1.4404

PRODUCT RANGE				
GMAE Part no.	Tube size (inch & mm)		Wall Thickness (inch & mm)	Weight
	O.D.	I.D.*		
10000548	1/4"	0,085"	0,083"	230gr/m
10000548	6,35	2,15	2,1	230gr/m
10000549	3/8"	0,130"	0,122"	500gr/m
10000549	9,53	3,31	3,11	500gr/m
10000550	9/16"	0,193"	0,185"	1127gr/m
10000550	14,3	4,9	4,7	1127gr/m

Transport

- In combination with 12-24MT garnet at no extra transport cost
- Transport without garnet on demand

Garnet Arabia Company Ltd does not provide any guarantee concerning the up-to-dateness, correctness or completeness of the information provided in this product data sheet. Liability claims against Garnet Arabia Company Ltd which relate to tangible or intangible losses which were caused due to use of the provided information or the use of defective and incomplete information are generally excluded. The above-mentioned exclusions of liability do not apply:

- if proven intentional or grossly negligent acts or omissions are present on the part of Garnet Arabia Company Ltd;
- in case of liability in accordance with the regulations of the Product Liability Act (Produkthaftungsgesetz) ie in case of injury to life body or health;
- in case of a breach of essential contractual obligations on the part of Garnet Arabia Company Ltd, unless injury to life, body or health is present. Should Garnet Arabia Company Ltd only breach essential contractual obligations in a simply negligent manner, the liability shall however be limited to losses which were foreseeable to Garnet Arabia Company Ltd at the time of conclusion of the contract or at the time of committing the breach of obligation. Essential contractual obligations are all obligations of Garnet Arabia Company Ltd whose fulfilment is essential in order to perform the contract and on whose compliance the customer regularly relies and may rely.